



**IT** Macchina rivettatrice automatica a motore elettrico per l'applicazione di rivetti con diametro della testa fra 3 e 20mm. Il caricatore facilmente intercambiabile permette l'applicazione di ogni tipo di rivetto. La gestione elettronica del motore e di tutte le funzioni è fatta da un microprocessore che incorpora sia un contatore parziale azzerabile che un contatore totalizzatore. Fra le opzioni d'uso la funzione movimento lento per PROVA e la funzione APPLICAZIONI MULTIPLE per la ripetizione di una sequenza programmabile per numero e velocità di applicazione.

Grazie alla sua grande profondità è particolarmente indicata per l'assemblaggio di casse in compensato pieghevoli mediante rivetti biforcati.

Della stessa macchina esistono versioni con profondità: 1200mm - 1500mm

**EN** Automatic riveting machine, electric motor, for rivets with head diameter between 3 and 20mm. The feeder, easily interchangeable allows to set every kind of rivet. All the functions are under the control of a microprocessor, a partial counter with reset and a total counter are available. Among the options a slow motion for TEST and a MULTIPLE SETTING to repeat a programmable sequence of a certain number of eyelets and the time between the setting.



Profondità / throat depth	850mm
Misure d'ingombro / Measures	500x1200x1500mm
Tempo di ciclo / Working cycle	0,35"
Alimentazione / Power supply	220V monof/single ph 800W
Peso / Weight	140 kg